

Benefits

- ❖ latest GEL technology
- ❖ totally maintenance free
- ❖ powerful and durable
- ❖ no gas leakage
- ❖ contains no liquid acid
- ❖ delivered in attractive sales cardboard



Details

ETN - NUMBER	DIN - NUMBER	JAPAN NUMBER	VOLTAGE VOLT	CAPACITY AH	LENGTH MM	WIDTH MM	HEIGHT MM	CIRCUIT	WEIGHT KG
GEL 503 0 14 003	503 14	CTX4L-BS	12	3	114	71	86	[- +]	1.7
GEL 504 0 11 002	504 11	CB4L-B	12	4	120	71	92	[- +]	1.8
GEL 504 0 12 003	504 12	CTX5L-BS	12	4	114	71	106	[- +]	1.9
GEL 505 0 12 006	505 12	CB5L-B	12	5	120	61	132	[- +]	2.0
GEL 506 0 14 005	506 14	CTX7L-BS	12	6	114	71	131	[+ -]	2.5
GEL 506 0 15 005	506 15	CTX7A-BS	12	6	152	88	94	[+ -]	2.9
GEL 506 0 16 013	506 16	YTZ 7S	12	6	113	70	105	[- +]	2.2
GEL 507 0 15 008	507 15	GT7B-4	12	6	150	65	92	[+ -]	2.4
GEL 508 0 12 008	508 12	CTX9-BS	12	8	152	88	107	[+ -]	3.1
GEL 508 0 15 011	508 15	GT9B-4	12	8	150	65	102	[+ -]	3.1
GEL 509 0 14 017	509 14	CB9-B	12	9	136	76	139	[+ -]	3.1
GEL 509 0 22 019	509 22	YTZ1 0S	12	8.6	150	87	95	[+ -]	3.1
GEL 510 0 12 009	510 12	CTX12-BS	12	10	151	87	131	[+ -]	4.0
GEL 510 0 13 009	510 13	CTX12A-BS	12	10	150	87	106	[+ -]	3.4
GEL 510 0 15 016	510 15	GT12B-4	12	10	150	69	130	[+ -]	3.9
GEL 511 0 20 021	511 20	YTZ 12S	12	11	150	87	110	[+ -]	3.7
GEL 511 0 21 023	511 21	YTZ 14S	12	11.5	150	87	110	[+ -]	3.9

Graphic explanations for battery connectors, circuits and floor strips can be found on the pages 89 to 94



contains no liquid acid

Panther GEL technology

12V motorcycle batteries with GEL technology.

High-end technology in the field of motorcycles. The Panther GEL-TECH contains no liquid acid and offers increased performance and durability.



Details

* For Harley Davidson

ETN - NUMBER	DIN - NUMBER	JAPAN NUMBER	VOLTAGE VOLT	CAPACITY AH	LENGTH MM	WIDTH MM	HEIGHT MM	CIRCUIT	WEIGHT KG
GEL 512 0 11 012	512 11	12N12A-4A1	12	12	134	80	161	[+ -]	4.7
GEL 512 0 14 010	512 14	CTX14-BS	12	12	151	87	145	[+ -]	4.7
GEL 514 0 11 014	514 11	CB14LA-2	12	14	135	90	161	[- +]	4.0
GEL 514 0 22 019	514 22	GT14B-4	12	12	150	69	145	[+ -]	4.4
GEL 519 0 13 017	519 13	BMW	12	19	186	82	171	[- +]	6.2
GEL 520 9 01 025 *	520 01	GHD20L-BS	12	20	175	87	151	[- +]	6.5
GEL 520 0 13 018	520 13	CTX20-BS	12	20	175	87	155	[+ -]	6.3
GEL 520 0 14 018	520 14	CTX20L-BS	12	20	175	87	155	[- +]	6.3
GEL 530 0 30 030	530 30	MG 53030	12	30	186	130	167	[- +]	9.3
GEL 530 0 36 030	530 36	YB30L-B	12	28	168	132	175	[- +]	9.5

Graphic explanations for battery connectors, circuits and floor strips can be found on the pages **89** to **94**

Properties

Product range	Motorcycle GEL	Characteristic	absolutely maintenance-free
Technology	GEL	Properties	low self-discharge
Condition	filled and charged	Usage	motorcycles, scooters, mopeds, ATV/quads, jetski, rideing mowers, snow mobiles
Quality	High-end / original equipment		



TECHNOLOGY BENCHMARK FOR VEHICLES

